


Conclusion

Please direct any questions or comments to Joseph M. Homa at (607) 974-9061.

Respectfully submitted,

CORNING INCORPORATED


Date: 5/9/02



Joseph M. Homa
Registration No. 40,023
Corning Incorporated
Patent Department
Mail Stop SP-TI-03-1
Corning, NY 14831

CERTIFICATE OF MAILING UNDER 37 C.F.R. § 1.8: I hereby
certify that this correspondence is being deposited with the United States
Postal Service as first class mail in an envelope addressed to Asst.
Commissioner of Patents and Trademarks, Washington, D.C. 20231 on
5/9/02

Date of Deposit

Joseph M. Homa
Name of applicant, assignee, or
Registered Representative


Signature
5/9/02

Date of Signature

VERSION WITH MARKINGS TO SHOW CHANGES MADE

RECEIVED

MAY 22 2002

TQ 2800 MAIL ROOM

36. (Canceled without prejudice) An optical waveguide fiber comprising:

a core region having a centerline and at least two segments having a positive relative refractive index, a refractive index profile, and an inner and an outer radius, the radii being measured with reference to the centerline;

a clad layer surrounding and in contact with the core region, the clad layer having a relative index and a refractive index profile;

wherein the optical waveguide fiber exhibits an optical attenuation at a wavelength of about 1383 nm which is not more than 0.10 dB/km above an optical attenuation exhibited at a wavelength of about 1310 nm.

37. (Canceled without prejudice) An optical waveguide fiber comprising:

a silica containing glass core; and

a glass cladding surrounding the silica containing glass core;

wherein the optical waveguide fiber exhibits an optical attenuation at a wavelength of about 1383 nm which is not more than 0.10 dB/km above an optical attenuation exhibited at a wavelength of about 1310 nm; and
wherein the optical waveguide fiber exhibits a zero dispersion at a wavelength greater than 1310 nm.